



Transmission Fluid

Technical Data Sheet



LOCOMOTIVE POWER ATF DEXRON III SYNTHETIC

PRODUCT DESCRIPTION:

LOCOMOTIVE ATF DEXRON III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, heavy duty automatic transmissions, power steering units and hydraulic systems requiring Dexron III G, MERCON and Allison C-4 fluids.

FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits.
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors.
- Especially effective in minimizing transmission "chatter." Helps ensure smooth, quiet action at all speeds.
- It ensures fast circulation during cold weather and excellent lubrication when hot.

PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON III G, III H • FORD MERCON V, FNR5 • FORD ESP-M2C-138-CJ/166-H
- MOPAR AS68RC • CHRYSLER ATF +3, ATF +4 • HONDA ATF Z-1
- HYUNDAI/KIA SP-II, SP-III, JWS 334/3317/3309 T4 • KIA RED-1 • IDEMITSU K17 • JASO 1A
- JWS 3309 • JWS 3324.TIV • MAZDA ATF-M III, ATF-MV
- MITSUBISHI DIAQUEEN ATF J2, J3, SP-II, SP-III, PA • NISSAN 402, NISSAN MATIC-D,J,K
- SUBARU ATF, ATF-HP • SUZUKI 3314, 3317 • TOYOTA T, T-II, T-III, T-IV (JWS 3309)
- AUDI G052 162, G052 990, G 055 025, G 052 540, G 055 005, G 055 162 • VW TL 52162
- BMW LA 2634, LT 71141 • ETL 7045E • ETL-8072B • MB 236.1 / 2 / 3 / 5 / 6 / 7 / 9 / 11
- MB 236.12 / 14 / 15 / 41 • PSA AL-4 • RENAULT DP-0 • TEXACO N402 • ZF TE-ML 09, 11A/11B
- ZF TE-ML 04D, 09, 11B, 1 4A, 14B, 16L, 17C • SAAB 3309 • VOLVO 4-6 SPEED • ALLISON TES 389
- ALLISON TES 228(C4) • MAZDA F-1/JWS 3317/ M-III/TYPE-IV • SUBARU HP

TYPICAL PROPERTIES:

PARAMETERS	TESTMETHOD	UNIT	DEXRON III
Grade			
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	35.22
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.25
Viscosity Index	ASTM D-2270	-	176
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.864
Flash Point (min)	ASTM D-92	°C	210
Pour Point	ASTM D-97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website www.locomotive.co.il